


Bucher FlexLine® CM100



Dimensions and weight (with chassis)¹

Lenght	9,584 mm
Height	3,530 mm
Width	2,550 mm
GVW	26,000 kg
TARE weight	Approx. 17,500 kg

Chassis^{2,3}

Scania	G 420 6x2*4
Cab type	CG17N
Wheelbase	4,350 mm
Mudguards	Plastic
Cyclist protection	Plastic
Rear underrun protection	R58.03

Superstructure item no. 90000041-F101 Chassis item no. 10000753

Dimensions and weight (without chassis)

Lenght (superstructure)	7,475 mm
Height (superstructure)	2,550 mm
Width (superstructure)	Max. 2,550 mm
Weight (superstructure)	9,000 kg

Engine⁴

Туре	DC13 176
Horsepower	420 HP
Emission level	Euro 6
Fuel	Diesel

Transmission

Power take-off	Half hydrau	ılic transmission
Jetting and vacuu	m pumps	PTO 1 and 2

Finish

Corrosion class	ISO 12	944 C3 medium
Undercarriage and	l components	Grey (RAL 7016)
Tank	W	/hite (RAL 9016)
Custom tank colo	ur ⁵	Option
Cabinets, shelves	, sign plates	Anodised
Slopped tray	Stair	nless steel (304)
Sign plates	3 pcs. painte	d in tank colour
Text and strippin	g Invo	iced separately

- ¹ Example with chassis listed in this data sheet. ² Chassis assigned to item no. 90000041-F101 ³ Other chassis (incl. electric) also possible.

- ⁴ Dependent on chassis. ⁵ According to standard paint sheet.

An all-round combination unit for the demanding user



Control panels

Set up, operate and adjust all functions with the control panels.



Frost protection

Protect your jetting system during winter with the 9 kW oil burner.



Small jetting hose reel

Ideal for smaller jobs and for cleaning of the vehicle.



Cabinets and Shelves

Keep things securely stored in the lockable cabinets with light & heat.

Bucher FlexLine® CM100

Tank

Gross volume	12.3 m ³
Operating pressure	1 bar

A pneumatically moved partition divides the tank in two variable water/sludge volume compartments.

Max. water/sludge vol. 10.5 m³ / 9.5 m³

Partition positions 3 lockable, 1 floating

Locking bolts 3 pairs, pneumatic

Water indicator Sight glass, and screen

Sludge indicator Mechanical float

End cover Hydraulic, fully automatic
Slopped tray Yes

Water filling valve
Suction valve at water filter

Bottom emptying valve water tank 2"

Jetting system

Pump	Uraca KD718
Capacity	333 l/min @ 170 bar
Jetting reel	Primary
Hose	200 m 1", plastic
Rotation/Swiv	el Hydraulic/Hydraulic
Jetting reel	Secondary
Hose	50 m ¾" + 60 m ½", plastic
Rotation/Swiv	el Hydraulic/Hydraulic

Vacuum system

Pump C	•	iable hydraulics) m³/h (942 cfm)
Top suction with dewat	n valve ering mesh	4", pneumatic
Bottom suc	ction valve	4", pneumatic
Cassette Hose Arm	2 m telesc	Hydraulic 4", rubber ope ext., 45° lift
Dewatering	g rear tank	Via cassette
Transport r		Hydraulic -10 m) 3", plastic

Controls

2"

3"

Controller	CAN-BUS
Control panels	3 pcs.
Remote control (12 functions)	1 pc.

Modem for remote access to control system for service/troubleshooting.

Storage

Cabinets, single	5 pcs.
Clothing cabinet	1 pc.
Cabinets supplied with heat.	
Shelves	2 pcs.
Toolboxes	2 pcs.

Lights

Work lights	5 pcs., LED
Beacon lights	2 pcs., LED
Flash lights	4 pcs., LED

Frost protection

Oil burner	9 kW
Jetting system circulation circuit	s Two

Equipment

- Vice
- Cover hook holder
- Protection guards for rear lights
- Handwashing station in cabinet
- Nozzle holders in cabinet 5 x 1/2" & 5 x 1"
- Extension ladder
- Safety fence holder

Accessories

- Safety support for rear end cover
- Rubber mat in cabinets and toolboxes
- Coupling transitions 4" to 3"
- Blowout hose for draining jetting system
- 4" suction pipe for cassette hose
- Cover hook set
- Safety fence
- Blind couplings 4"
- Standard nozzles $\frac{1}{2}$ " and 1"

Contact us for more information.

Bucher Municipal



For local contact and support, please scan the QR code or visit

buchermunicipal.com





