


# Bucher Recycler® RM140 super



## Dimensions and weight (with chassis)<sup>1</sup>

Lenght	10,333 mm
Height	3,510 mm
Width	2,550 mm
GVW	32,000 kg
TARE weight	Approx. 20,940 kg

## Chassis<sup>2,3</sup>

Scania	P 460 8x2*6NA
Cab type	CP20N
Wheelbase	5,550 mm
Mudguards	Plastic
Cyclist protection	Alu. rails
Rear underrun protection	R58.03

90000040-F101 Item no. superstructure 10000435

## Dimensions and weight (without chassis)

7,950 mm
2,530 mm
Max. 2,550 mm
11,000 kg

## Engine<sup>4</sup>

Туре	DC13 175
Horse power	460 HP
Emission level	Euro 6
Fuel	Diesel

## Transmission

Power take-off From engine and gearbox Jetting/Vacuum pumps Belt/Hydraulic driven

## **Finish**

Corrosion class	ISO 12	944 C3 medium
Undercarriage and	d components	Grey (RAL 7016)
Tank	V	hite (RAL 9016)
Custom tank cold	our <sup>5</sup>	Option
Cabinets, shelve	s, sign plates	Anodised
Slopped tray	Stand	ard steel (S235)
Sign plates	3 pcs., painte	d in tank colour
Text and strippin	ig Invo	iced separately

- <sup>1</sup> Example with chassis listed in this data sheet. <sup>2</sup> Chassis assigned to item no. 90000040-F101
- <sup>3</sup> Other chassis (incl. electric) also possible.
- <sup>4</sup> Dependent on chassis. <sup>5</sup> According to standard paint sheet.

## The market's most powerful recycling system



## **Control panels**

Set up, operate and adjust all functions with the control panels.



#### Accessories

Extend your unit's capabilities with a wide range of accessories.



#### Continuous recycling system

Save resources while increasing productivity and sustainability.



#### **Cabinets and Shelves**

Store your gear in the shelves and lockable cabinets.

## Bucher Recycler® RM140 super

#### Tank

Gross volume	14.7 m <sup>3</sup>
Operating pressure	1 bar

A pneumatically moved partition divides the tank in two variable water/sludge volume compartments.

Max. water/sludge vol. 12.7 m<sup>3</sup> / 11.9 m<sup>3</sup> Partition positions 3, lockable Locking bolts 3 pairs, pneumatic

Water indicator Clear pipe, and screen Sludge indicator Mech. float, and screen Hydraulic, fully automatic End cover Slopped tray Water filling 2" valve, free fall Bottom emptying water tank 3" valve

## Jetting system

Pump	Uraca P3-45
Capacity	482 l/min @ 150 bar
1st. Jetting ree	el Hydraulic
Hose	200 m 5⁄4", plastic
2nd. Jetting re	el Hydraulic
Hose	50 m ¾" + 60 m ½", plastic

#### Vacuum system

Pump	CVS WR 3100
Capacity	3,100 m <sup>3</sup> /h (1,825 cfm)
Pump (deep su	uction) CVS 400 ssure) 345 m³/h (203 cfm)
Top suction	5" valve, pneumatic
Bottom suction	6" valve, pneumatic
Cassette	Hydraulic
Hose	6", rubber
Arm	2 m telescope ext., 45° lift

## Water recycling system

Pump Vogelsang VX136-105Q NBR HiFlo Two. Coarse and fine Recycling 5-step, automatic, continuous

The pump can be used as a transfer pump. The system can be turned off so it can be used as a regular combination unit.

#### **Controls**

Controller	CAN-BUS
Control panels	3 pcs.

Modem for remote access to control system for service/troubleshooting.

#### Storage

Cabinets, double	2 pcs.
Cabinets, single	2 pcs.
Shelves	3 pcs.

#### Lights

CVC MID 2100

Work lights	5 pcs., LED
Beacon lights	2 pcs., LED

#### Frost protection

Air pressure draining and cleaning - incl. blow out air hose.

#### Equipment

- Vice
- Cover hooks holder
- Protection guards on rear lights
- Handwashing station in cabinet

#### Accessories

- Safety support for rear end cover
- Rubber mat in cabinets and tool boxes
- Coupling transitions 6" to 4" and 5" to 4"
- Blind couplings 5" and 6"
- Blowout hose for draining jetting system
- 1.5 m 3" hose w/ couplings for cleaning filter unit, incl. transition 3" to 2"
- 5 m 4" suction hoses with couplings
- 6" suction pipe for cassette hose
- 6" suction pipe w/ 2" air injection incl. 20 m (4x5 m) 2" hose (deep suction)
- Cover hooks set
- Extra water filters for jetting pump
- Nozzle set 3/4" recycled water

Contact us for more information.

#### **Bucher Municipal**



For local contact and support, please scan the QR code or visit

buchermunicipal.com