



Experience the power of continuous recycling: Increase productivity and sustainability

RECycler® 414




Hvidtved Larsen www.hvidtved.com

RECycler® 414

The market's most powerful recycling system

Made for the business that matters. Yours.


With the RECycler®, you are ready for the most demanding tasks faced in the industry. With our 5-step world-leading recycling system, you get the market's most effective system that in continuous operation ensures you can clean the pipes easier, faster and more cost effective.



Technical specifications

Technical specifications	
Tank	 14,000 litres (3,079 UK gal) Approved for 1 bar pressure Movable partition, pneumatic 3 sets of locking bolts, manual 4" top suction and 6" bottom suction, manual Fully automatic end cover, hydraulic
Water	 Uraca 718, 390 l/min @ 140 bar (85 UK gpm @ 2030 psi) Primary hose reel with 150 m 5/4" thermoplastic jetting hose, hydraulic Secondary hose reel with 50 m 3/4" and 60 m 1/2" thermoplastic jetting hose, hydraulic Hydraulic swivels Water filter for protection of pump Recycling system with Desmi pump
Vacuum	 CVS VacuStar 1600 - oil cooled and equipped with a lubrication pump 941 cfm (5,866 UK gpm) @ free flow / 924 cfm (5,756 UK gpm) @ 60% vacuum 5" suction cassette with hydraulic lift and double telescopic arm
Control	 BUS-based PLC 2 control panels, one mounted on the back of the tank and one on the side
Chassis	Scania P410 B 8x4, CP17L medium day cab, with rear view camera and navigation
Lights and reflectors	 5 work lights, LED 2 flash lights, LED 1 flash bar, LED 6 side lights with built-in reflectors, LED
Cabinets and shelves	 1 double cabinet with hand wash facility 1 tool cabinet 2 hose shelves 2 tool shelves
Accessories	 1 nozzle set 4x5 m 4" hoses including Bauer couplings 1.5 m 3" hose with coupling for cleaning filter unit 1 Bauer reduction 6" male to 4" female, 1 Bauer reduction 5" male to 4" female 1 end cover safety support
Finish	 Cabin and tank: Ivory white Chassis: Scania Sub Grey 8 step painting process (Corrosion class C3, Tank: 200-300 μm, Rest: 100-120 μm) Text and striping invoiced separately

The movable partition and recycling system provide the means to increase efficiency in jetting, water filling and driving by $55\,\%$



J. Hvidtved Larsen UK Ltd. Unit 1, Samson Road Leicestershire LE67 3FP Phone.: +44 1530 815687 info@hvidtved.com

www.hvidtved.com