



An all-round multipurpose unit tested and optimized to improve efficiency in time and fuel consumption

FlexLine® 306



FlexLine® 306

Flexibility and accessibility improved

Good fuel economy

With hydraulically driven pumps the fuel consumption is kept at minimum level

Low maintenance costs

Bolted joints, parts from international suppliers and BUS reduce repair costs

Accesibility

By virtue of size, FlexLine® 306 is the optimum choice for populated areas

A powerful machine

Despite its size, the FlexLine® 306 can solve the most demanding tasks

Flexibility is a priority

A moveable partition provides a flexible tank size and flexibility of applications

Optimal performance

Optimal performance is ensured with digital displays and an intuitive operation

Technical specifications

Tank	 6,000 litres Approved for 0.5 bar pressure Movable partition, pneumatic 1 set of locking bolts, manually 4" top and bottom suction, manually Fully automatic end cover, hydraulic
Water	 Uraca P3-15, 207 l/min @ 160 bar Hose reel with 150 m 3/4" thermoplastic jetting hose, hydraulic Hydraulic swivels NDD pump type: Udor CKC 17/28, 17 l/min @ 280 bar NDD hose reel: 25 m 3/8" with spring reaction, manual Water filter for protection of pump
Vacuum	 CVS VacuStar WR 3100 - liquid ring pump with intercooler Max capacity 51,667 l/min 5" suction cassette, hydraulic Hydraulic boom, 2000 mm extension and 16000 mm lift
Control	BUS-based PLC 2 control panels, one mounted on the back of the tank and one on the side Remote control
Chassis	• HINO 6X4 supplied by Bucher Municipal Pty Ltd.
Lights and reflectors	• 5 work lights, LED • 2 flash lights, LED • 1 flash bar, LED • 6 side lights with built-in reflectors, LED • ADR conspicuity reflectors
Cabinets and shelves	1 double cabinet fitted with hand wash facility1 tool cabinet2 hose shelves, 2 tool shelves
Accessories	• 1 nozzle set • Detachable vice • 1 cover hooks • 1 end cover safety support • 6" cassette suction pipe • 1 Camlock reduction 6" male to 4" female • NDD jetting gun: 2 m lance and Roto-jet nozzle • 1.5m 3" hose with coupling for filterunit cleaning. Blow out air hose with couplings for jetting system draining
Finish	 Cabin and Tank: Ivory White Chassis: Anthracite Grey 8 step painting process (Corrosion class C3, Tank: 200-300 μm, Rest: 100-120 μm) Text and striping invoiced separately

With a movable partition, you will get world-class flexibility. And world-class flexibility is great for the business that matters. Yours.

