


# CityCat 5006

Performance package in the compact class







# High performance and productivity

The CityCat 5006 delivers on performance. It has the appetite of a large truck mounted sweeper, the functionality of a multi-purpose vehicle and the maneuverability of a compact sweeper; all delivered in a single package, designed and built to the exacting standards required by demanding municipal environments.

The smooth-running, high-torque Iveco engine with extremely low fuel consumption and emission levels allows exceptionally reliable and economical operation. Heavy-duty suction power and a high payload are combined with a four-wheel steering system as standard, to provide capacity and agility without

compromise. Comfortable in heavy-duty cleansing environments and crowded streets, the CityCat 5006 easily cleans urban areas.

With the 7.3 YD<sup>3</sup> stainless steel hopper, and an optional water recirculation feature, the CityCat 5006 achieves increased on-station working and reduces 'tip runs', enhancing productivity and reducing running costs.

The two side brushes in combination with a 3rd brush have a maximum sweeping width of 148" (3768 mm). The sweeping system can be hydraulically moved 15" (400 mm) laterally to the left or right-hand side of the sweeper.

#### **EcoELS**

Engine & hydraulic management system

### Low fuel consumption


According to EN 15429-2 standard

### Class leading turning circle

232" curb to curb

### High payload

Up to 11,023 lbs at 23.150 lbs GVM



# The CityCat 5006 delivers



#### Traveling speed

Up to 31 mph

#### Steering

Hydrostatic controlled four-wheel steering

#### **Hydrostatic drive**

Can switch seamlessly from forward to reverse and work mode/transit

#### **Easy clean option**

Available for easier cleaning of the hopper, reducing daily cleaning effort



#### **Water tanks**

Optimized moulded design with easy removal for maintenance

#### Pick up system

Pulled brush system with suction intake in front of axle, hydraulically and laterally movable

#### Steel hydraulic pipes

Up to 60% less hydraulic hoses than other sweepers in this class



#### **Hopper**

7.3 YD³ stainless steel hopper volume with high dump option

#### Water volume

232 gallon water capacity



#### **Disc brakes**

Front axle with dual calipers, rear axle with single calipers

#### Water recirculation

Service water is filtered and fed to the suction intake

#### **EcoELS**

Unique engine and hydraulic Eco Extended Load Sensing management system, which allows a reduction of noise and fuel consumption with no loss of performance



#### **Battery isolator switch**

Allows safe working and prevents an accidental discharge







### Low environmental **impact**

#### Low water usage

The CityCat 5006 uses a recirculation system to reuse the water inside the hopper. This reduces refilling costs and extends on-station time.

#### Low fuel consumption with EcoELS

Through the intelligent EcoELS engine and hydraulic management system, the CityCat 5006 can provide a high energy efficiency, high performance and low noise, resulting in optimum fuel consumption. The concept considers the performance requirements of the operator and external influences such as sweeping mode or driving uphill, automatically delivering the amount of power needed for the task, without derating the optimal operating point. Comparison tests have shown a reduction of diesel consumption between 25-30% and a noise level of 20%.

#### Less CO<sub>2</sub> emissions

With its low fuel consumption in work mode, the CityCat 5006 produces only half as much CO<sub>2</sub> emissions per year as other sweepers in its class (per year = 2,000 operating hours).

#### **Dust emissions**

EUnited 4 star certified for PM10 and PM2.5.

#### **HVO / Bio diesel B7 compatible**

HVO (Hydrotreated Vegetable Oil) has the equivalent productive output as diesel but with none of the harmful properties. It burns cleaner and produces significantly lower damaging emissions, with up to 90% less Carbon Dioxide (CO<sub>2</sub>) and 30-70% less NOX (nitrogen oxides). A non-fossil fuel, HVO can be used 100 % or with any EN590 diesel mix without modification or change in servicing requirements.

#### High dust suppression

Water jets on each brush provide a fine clean water spray to trap dust particles lifted by the two (optional three) brushes. In addition, recycled water from the hopper is filtered and fed into the suction intake.

**Iveco NEF** Tier 4 Final Engine

Standard engine

PM10 and PM2.5

**EUnited 4 star** certified



# **Safety** and comfort

Bucher Municipal is dedicated to achieving the highest productivity from its sweepers. We believe enhanced operator comfort and safety directly relate to productivity and equipment performance. That is why our sweepers are designed to give the best driver comfort and ease of operation, as well as providing a safe work environment for the driver and for third parties.

The compact outer dimensions, as well as the fourwheel steering system that can be turned on and off, give the CityCat 5006 maximum maneuverability, ensuring perfect directional stability and safety for everyday work.

#### Safe handling

- Cruise control option in work mode reduces operator effort
- Hydrostatic drive system auto brakes when the driver disengages drive
- All-round disc braking system (front and rear) and hydraulic operated disc handbrake system

#### All-round control

- An audible signal for safe reversing
- Rear view camera auto engages when reverse is selected

#### **Operators comfort**

- Low in-cab noise
- Comfortable, hydro bearing cab suspension
- Steering column with angle and height adjustment
- Full automotive suspension

#### The cab design

The cab design of the CityCat 5006 achieves space, wide screen visibility, ease of use and comfort, from a range of standard and optional benefits:

- 3 person cab
- Air-suspension adjustable seat with lumbar support and optional heating
- Soft-feel steering wheel with angle adjustment
- Power-assisted steering
- Heated, curved and low-reflection windscreen
- Integrated air conditioning option
- In-cab heating
- In-cab radio and MP3 player



#### Visual module

The display gives information on sweeper functions and has also a diagnostic fault finding capability. Fault diagnosis is also accessible from the visual module.



#### Cabin

Walk through cab with clear side vision and big windscreen. Easy reach/use control panels positioned to the front and side of the operator.



#### **Operator safety**

Automatically engaged mechanical high visibility body prop.



#### **Multi-functional armrest**

The multi-function and adjustable armrest enable operators to control the sweeping functions of the machine from a single large buttoned keypad.



#### **Central console**

Easy to reach with water tabs, hand brake, power plug and air-conditioning controls.



#### 3 person cab

Optional third passenger seat allowing transportation of additional crew members.



### Low cost of ownership

The CityCat 5006 offers lower maintenance costs when compared to a chassis mounted vehicle. With 500-hour service intervals on the whole vehicle, service costs and downtime are kept to a minimum.

Designed to cope with tough environments, the CityCat 5006 hopper is manufactured from 1.4003 stainless steel for protection against corrosion and wear.

The CityCat 5006 is designed and built for urban and city sweeping. The engine and drive train are also matched to this purpose, resulting in greater fuel efficiency.

Bucher Connect offers digital alerts or recommendations whenever you experience a fault or error. Our service also includes access to technical assistance for real-time solutions and remote diagnostics, which drastically reduces maintenance costs and increases operating time.

#### Water volume

Water recirculation option and 232 gal clean water volume - allowing prolonged productive work time

#### Fan

Heavy-duty fan with wear resistant blades


#### Multi-season

Year-round multi-tasking machine Bucher Connect



### Sweep and suction system

High productivity starts with the interaction of driver and equipment. The sweeping system combined with a large water and hopper volume are the basis for achieving this goal. The pulled brush system with 15.75" lateral adjustment is easy to maneuver so the driver can focus on the road and the optional 3<sup>rd</sup> brush.



- 1 Large, easy to clean mesh inside the hopper to prevent clogging by leaves
- 2 Large 7.3YD<sup>3</sup> stainless steel hopper with water recirculation system
- 3 Fan arrangement on top of the hopper for optimal air flow
- 4 Bucher DNA straight suction hose with water nozzles for dust suppression
- 5 Big 232 gallon fresh water volume with tank placement for a low point of gravity
- 6 Recirculation system which feeds the used water directly to the suction intake

- 7 Wide 31" (800 mm) suction intake, laterally adjustable
- 8 Pulled brush system, whole system laterally adjustable
- 9 Water nozzles for maximum dust suppression, adjustable from cab

### Significant options



#### **Road construction brush**

The road construction front brush is suitable for particularly tough applications, including road construction and weed removal. Furthermore, it has a floor support pressure regulation and a tilt.



#### Boom reel & hand lance

Two booms are mounted on the hopper with a reel and a hand lance that are connected to the highpressure water system, useful for flushing rubbish from the sides of the street directly in front of the sweeper.



#### Wanderhose

The wanderhose with hydraulic support enables cleaning of underfloor containers up to 6.5 feet deep. The abrasion resistant, 360° rotatable suction hose has a diameter of 8" with a length of 21 feet.



#### **Traveling Speed 31 mph**

Traveling speed is set to a maximum of 31 mph with a mechanical steering system replacing the hydraulic steering system.



#### Street wash system

Ample pressure allows market squares, building sites and pedestrian zones to be washed down and left spotlessly clean.




#### High dump

Allows the sweeping material to be dumped into dumpsters or dump trucks by having an extended discharge height of 61".



# Sweeper configuration



#### Dimension

Dimensions		
Length	194" (4945 mm)	
Width	70" (1798 mm)	
Height	98" (2500 mm)	
Wheelbase	96" (2450 mm)	
Track	59" (1513 mm)	
Max. cleaning width 2 brushes	99" (2533 mm)	
Max. cleaning width 3 brushes	138" (3520 mm)	
Max. cleaning width 3 brushes (RCB)		
	148" (3768 mm)	
Turning radius	116" (2950 mm)	

#### Tires

#### 265 / 70 R 19.5 140 / 138M

\* According to national legislation

#### Noise level cab

63 dB(A)

Driving Performance		
Working speed	0-12 mph	
Travelling speed	0-49 mph*	
Climbing ability	30%	

#### Chassi

Bucher fabricated ladder frame chassis with
"C" rail construction.

GVW 23,148 / 22,928 lbs (49 mph)

Empty weight 12,125 / 12,345 lbs (49 mph)

Payload 11,023 / 10,802 lbs (49 mph)

#### **Engine**

Engine	FPT, Iveco	NEF Tier 4 Final 141 HP
Engine displace	ement	4485 cm <sup>3</sup>
Output		141 HP @ 2,200 RPM
Torque		427 ft lbs (608 Nm)
Fuel tank		29 gal
Electrical syste	m	24 V





#### **Bucher Municipal North America Inc.**

105 Motorsports Road Mooresville, NC 28115 Tel. +1 704 658 1333 Fax +1 704 658 1377 info.us@buchermunicipal.com

#### www.buchermunicipal.com

At Bucher Municipal, we innovate and engineer better cleaning and clearing solutions, helping our customers grow and maintain efficient and profitable businesses. Leveraging the over 200-year-old heritage of Bucher, we are committed to helping you achieve more using less. Taking pride in being seen as a reliable partner, we work locally with you in realizing the possibilities for a smarter, cleaner and more efficient tomorrow. Today.















#### Scan for your free report



The 5 Things You <u>Must</u> Know Before Buying a Street Sweeper